

## Sending variables via rsh which contains "\$"

*Source:* <http://unix.derkeiler.com/Mailing-Lists/AIX-L/2005-08/0099.html>

---

**From:** Alberto Cozer (*acozer\_at\_UOL.COM.BR*)

**Date:** 08/17/05

Date: Tue, 16 Aug 2005 20:49:36 -0300  
To: aix-l@Princeton.EDU

Hello Everybody,

Does anybody knows how to make a shellscript pass a variable which contains "\$" followed by a number, without having it changed to null?

Example:

- 1) root@server1:/usr/local/bin/ # echo test\*\$89  
test\*9
- 2) root@server1:/usr/local/bin/ # echo 'test\*\$89'  
test\*\$89
- 3) root@server1:/usr/local/bin/ # rsh server2 echo test\*\$89  
test\*9
- 4) root@server1:/usr/local/bin/ # rsh server2 echo 'test\*\$89'  
test\*9

Command #4 doesn't work as expected and always converts the \$8 to null. Already tryed changing the '' to '\ ' as well as a lot of other weird combinations with ', ', `', and ", without success. Any help will be highly appreciated.

Thanks a bunch,  
Alberto.

=====  
Alberto Cozer  
Systems Security Eginer  
Check Point Certified Security Expert, CCSE NG  
IBM Certified AIX Specialist