

# Re: Syslog host

---

*Source:* <http://unix.derkeiler.com/Mailing-Lists/AIX-L/2007-11/msg00018.html>

---

- *From:* Robert Binkley <[leebinkley@xxxxxxxxx](mailto:leebinkley@xxxxxxxxx)>
  - *Date:* Fri, 9 Nov 2007 05:59:19 -0800
- 

like this

```
*.crit /tmp/syslog.out @10.10.10.2
```

----- Steve Stackwick <[sstackwick@xxxxxxxxx](mailto:sstackwick@xxxxxxxxx)> wrote:

In /etc/syslog.conf on 10.10.10.1, you can set a destination host for messages by specifying @10.10.10.2 (in your example).

There's an example if you man syslogd.

Steve

On 11/8/07, Robert Binkley <[leebinkley@xxxxxxxxx](mailto:leebinkley@xxxxxxxxx)> wrote:

Hello

Currently I have be asked to send my syslog from

aix

to another system

so say serve a going to server b  
A server = 10.10.10.1 B=10.10.10.2

how can this be done

---

Stephen Stackwick  
Jacob & Sundstrom, Inc.  
401 East Pratt St., Suite 2214  
Baltimore, MD 21202-3003  
(410) 539-1135 \* (866) 539-1135  
[sstackwick@xxxxxxxxx](mailto:sstackwick@xxxxxxxxx)