

Re: [HEADSUP] naming of tty devices.

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/arch/2004-09/0136.html>

From: Poul-Henning Kamp (*phk_at_phk.freebsd.dk*)

Date: 09/20/04

To: Ruslan Ermilov <ru@freebsd.org>
Date: Mon, 20 Sep 2004 11:02:07 +0200

In message <20040920085908.GA43176@ip.net.ua>, Ruslan Ermilov writes:

>>
>> *sio's cuaa* gets renamed to cuad**
>>
>> *sio's {tty,cua}[il]%d gets renamed to {tty,cua}%d.{init,lock}*
>>
> *But we now have cuaa0, cuaia0, cuala0, ttyd0, ttyid0, and ttyld0.*
> *So, shouldn't the above line be instead:*
>
> *sio's tty[il]d%d gets renamed to ttyd%d.{init,lock}*
> *sio's cua[il]a%d gets renamed to cuad%d.{init,lock}*
>
> *You didn't make it clear what \${base_device} should look like, but I'm*
> *sure you meant that will it include the driver's "letter". This way*
> *we'll have: ttyd0, ttyd0.init, ttyd0.lock, cuad0, cuad0.init, cuad0.lock.*

OOps: forgot to say: yes, you're right.

--

Poul-Henning Kamp | UNIX since Zilog Zeus 3.20
phk@FreeBSD.ORG | TCP/IP since RFC 956
FreeBSD committer | BSD since 4.3-tahoe
Never attribute to malice what can adequately be explained by incompetence.

freebsd-arch@freebsd.org mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-arch>

To unsubscribe, send any mail to "freebsd-arch-unsubscribe@freebsd.org"