

freebsd-arch: Re: [CFR] reflect resolv.conf update to running application

Re: [CFR] reflect resolv.conf update to running application

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/arch/2005-08/0200.html>

From: Hajimu UMEMOTO (ume_at_freebsd.org)

Date: 08/22/05

Date: Tue, 23 Aug 2005 00:34:28 +0900

To: Brooks Davis <brooks@one-eyed-alien.net>

Hi,

>>>> *On Mon, 22 Aug 2005 08:12:54 -0700*

>>>> *Brooks Davis <brooks@one-eyed-alien.net> said:*

brooks> I'm fine with the cmp version of the change so long as you only perform
brooks> the test if /usr/bin/cmp exists. dhclient-script may be called before
brooks> /usr exists and must not misbehave under those circumstances.

If /usr/bin/cmp does not exist, The whole test will fail, then it will work as heretofore. So, I think we don't need to test if /usr/bin/cmp exists.

However, if /usr/bin/cmp does not exist, error message will out. So, we need to suppress it as following:

```
if cmp -s /etc/resolv.conf.std /etc/resolv.conf; then
    rm -f /etc/resolv.conf.std
    return 0
fi 2>/dev/null
```

Sincerely,

--

Hajimu UMEMOTO @ Internet Mutual Aid Society Yokohama, Japan

ume@mahoroba.org ume@{,jp.}FreeBSD.org

<http://www.imasy.org/~ume/>

freebsd-arch@freebsd.org mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-arch>

To unsubscribe, send any mail to "freebsd-arch-unsubscribe@freebsd.org"