

freebsd-current: confirm subscribe to phpwizard@rent-a-phpwizard.de

confirm subscribe to phpwizard@rent-a-phpwizard.de

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/current/2003-06/0042.html>

phpwizard-help_at_rent-a-phpwizard.de

Date: 06/01/03

Date: 1 Jun 2003 14:35:03 -0000

To: current@freebsd.org

Hi! This is the ezmlm program. I'm managing the
phpwizard@rent-a-phpwizard.de mailing list.

To confirm that you would like

current@freebsd.org

added to the phpwizard mailing list, please send
an empty reply to this address:

phpwizard-sc.1054478103.hadcmplemfmehciakb-current=freebsd.org@rent-a-phpwizard.de

Usually, this happens when you just hit the "reply" button.
If this does not work, simply copy the address and paste it into
the "To:" field of a new message.

This confirmation serves two purposes. First, it verifies that I am able
to get mail through to you. Second, it protects you in case someone
forges a subscription request in your name.

--- Administrative commands for the phpwizard list ---

I can handle administrative requests automatically. Please
do not send them to the list address! Instead, send
your message to the correct command address:

To subscribe to the list, send a message to:

<phpwizard-subscribe@rent-a-phpwizard.de>

To remove your address from the list, send a message to:

<phpwizard-unsubscribe@rent-a-phpwizard.de>

Send mail to the following for info and FAQ for this list:

<phpwizard-info@rent-a-phpwizard.de>

<phpwizard-faq@rent-a-phpwizard.de>

confirm subscribe to phpwizard@rent-a-phpwizard.de

frebsd-current: confirm subscribe to phpwizard@rent-a-phpwizard.de

To get messages 123 through 145 (a maximum of 100 per request), mail:

<phpwizard-get.123_145@rent-a-phpwizard.de>

To get an index with subject and author for messages 123-456 , mail:

<phpwizard-index.123_456@rent-a-phpwizard.de>

They are always returned as sets of 100, max 2000 per request, so you'll actually get 100-499.

To receive all messages with the same subject as message 12345, send an empty message to:

<phpwizard-thread.12345@rent-a-phpwizard.de>

The messages do not really need to be empty, but I will ignore their content. Only the ADDRESS you send to is important.

You can start a subscription for an alternate address, for example "john@host.domain", just add a hyphen and your address (with '=' instead of '@') after the command word:
<phpwizard-subscribe-john=host.domain@rent-a-phpwizard.de>

To stop subscription for this address, mail:

<phpwizard-unsubscribe-john=host.domain@rent-a-phpwizard.de>

In both cases, I'll send a confirmation message to that address. When you receive i