

Re: tcsh backtick hang info

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/current/2007-07/msg00659.html>

- *From:* Giorgos Keramidas <keramida@xxxxxxxxxxx>
 - *Date:* Sat, 14 Jul 2007 03:55:59 +0300
-

On 2007-07-12 14:56, Christos Zoulas <christos@xxxxxxxxxxx> wrote:

On Jul 12, 11:48am, dwhite@xxxxxxxxxxx (Doug White) wrote:
— Subject: Re: tcsh backtick hang info

| Thanks for the good words, Christos! If you can confirm this will be the
| official patch then we can apply it to our vendor sources. If there are
| any other fixes for nasty bugs in 6.15.00 that you're hanging on to it'd
| be good to get those out and imported as well.

You are welcome!

This will be the official patch, and yes I have another 9 bug fixes since 6.15.00. In general, I don't make 6.15.XX generally available, but the severity of some of those problems fixed is high enough to possibly justify a 6.16.00 sooner than later. Here's the list of fixes:

10. kill `foo` got stuck because sigchld was disabled too soon (Mark Peek)
9. Avoid null pointer dereference in proc cwd (Kurt Miller)
8. eval "foreach a b c" exits (Anthony Menasse)
7. Quoting was broken in substitutions (Joe Wells)
6. QNX patches via pkgsrc
5. cd – twice from a directory that contained a glob pattern, expands the glob twice (Mark Santcross)
4. MidnightBsd support (Lucas Holt)
3. Fix history substitution core-dump with no history entries
2. Merge two character tables that are the same (Martin Kraemer)
1. On ancient 7 bit locales, punctuation characters are used to denote special characters such as umlaut, adiaresis, etc. These characters return true for isalpha/isalnum. Ignore them because they break parsing (Martin Kraemer)

Hi Christos,

Can we persuade you to include the following local patch I keep for autologout detection with /dev/pts/XXX pty's in FreeBSD?

%%%

Fix pty detection logic of tcsh autologout initialization.

Re: tcsh backtick hang info

Noticed by: kris

```
diff --git a/contrib/tcsh/sh.c b/contrib/tcsh/sh.c
--- a/contrib/tcsh/sh.c
+++ b/contrib/tcsh/sh.c
@@ -457,7 +457,7 @@ main(int argc, char **argv)
if (*cp) {
/* only for login shells or root and we must have a tty */
if ((cp2 = Strchr(cp, (Char) '/')) != NULL) {
- cp = cp2 + 1;
+ cp2 = cp2 + 1;
}
else
cp2 = cp;
%%%

```

freebsd-current@xxxxxxxxxxxxx mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-current>

To unsubscribe, send any mail to "freebsd-current-unsubscribe@xxxxxxxxxxxxx"