

Re: repeatedly opening the same .so(s) is slow?

Re: repeatedly opening the same .so(s) is slow?

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/hackers/2006-03/msg00207.html>

- *From:* joerg@xxxxxxxxxxxxxxxxxxxx
 - *Date:* Tue, 21 Mar 2006 19:43:05 +0100
-

On Wed, Mar 22, 2006 at 05:07:29AM +1100, Peter Jeremy wrote:

On Tue, 2006-Mar-21 14:31:24 +0100, joerg@xxxxxxxxxxxxxxxxxxxx wrote:

Set `libltdl_cv_sys_dlopen_deplibs=yes` in the environment before running configure and try again. And yes, this is **exactly** the same idiosyncraty as KDE.

This is needed for both guile and libltdl. After replacing libltdl and libguile-ltdl, gnucash startup has dropped from 15 minutes to 10 seconds. Thanks for the pointer. The correct fix would be to patch the configure script so it recognizes FreeBSD. I'll file a PR this evening (if no-one has fixed it by then).

If you report it upstream, please ask them to either drop this check or write an actual test case. I don't even know a platform where it is broken, so hurting platforms where no developers is using it just sucks :-)

Joerg

freebsd-hackers@xxxxxxxxxxxx mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-hackers>

To unsubscribe, send any mail to "freebsd-hackers-unsubscribe@xxxxxxxxxxxx"