

Re: sendmail sasl configuration

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/isp/2003-08/0133.html>

From: Jamie (jamie_at_gnulife.org)

Date: 08/23/03

Date: Sat, 23 Aug 2003 13:45:03 -0500 (CDT)

To: freebsd-isp@freebsd.org

On Sat, 23 Aug 2003, Sean Ellis wrote:

>
> *Connected to localhost.linwoodhomes.com.*
> *Escape character is '^]'.*
> *220 xxxxxxxxxxxx.com ESMTP Sendmail 8.12.2/8.12.2; Sat, 23 Aug 2003 11:27:17 -0700 (PDT)*
> *ehlo localhost*
> *250-xxxxxxxxxxx.com Hello localhost.xxxxxxxxxx.com [127.0.0.1], pleased to meet you*
> *250-ENHANCEDSTATUSCODES*
> *250-PIPELINING*
> *250-EXPN*
> *250-VERB*
> *250-8BITMIME*
> *250-SIZE*
> *250-DSN*
> *250-ETRN*
> *250-AUTH LOGIN*
> *250-DELIVERBY*
> *250 HELP*
>
> *and the following log error appears when restarting sendmail:*
>
> *error: safesasl(/usr/local/etc/sasldb.db) failed: Permission denied*
>
> *file is:*
>
> *-rw-r----- 1 cyrus wheel 16384 Aug 22 17:23 /usr/local/etc/sasldb.db*
>
> *sendmail.mc options were taken from the freebsd handbook page on the*
> *topic.*
>
> *Can anyone steer me in the right direction here?*
> --
> *Thanks,*
> *Sean <mailto:sellis@telus.net>*

freebsd-isp: Re: sendmail sasl configuration

Sorry about the top post in my reply. I'm trying to get out of that nasty habit. :)

It looks like the compilation worked.

Do you have this in line in your sendmail.mc file?

```
define(`confAUTH_MECHANISMS', `PLAIN CRAM-MD5 DIGEST-MD5 LOGIN')dnl
```

– Jamie

freebsd-isp@freebsd.org mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-isp>

To unsubscribe, send any mail to "freebsd-isp-unsubscribe@freebsd.org"