

Re: vpopmail POP: "ERR aac, chiled crashed" after reboot, core dumped

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/isp/2003-09/0091.html>

From: Chris Shenton (chris_at_shenton.org)

Date: 09/15/03

To: vchkpw@inter7.com

Date: Sun, 14 Sep 2003 21:25:11 -0400

Self-follow-up, hopefully useful.

I truss the process running the POP tcpserver, then the process it forks when I connect to the POP port. I don't know if the ERR#9 is fatal, and unfortunately can't trace the next forked process 33323 because the child crashes immediately after displaying the info.

Does this help at all? Thanks.

```
mahe# ps -axww|grep tcpser
33265 ?? S 0:00.00 tcpserver -v -u 82 -g 65533 0 smtp /var/qmail/bin/qmail-smtpd
276 p0- S 0:03.25 tcpserver -v -u 82 -g 65533 0 smtp /var/qmail/bin/qmail-smtpd
32797 p1 I 0:00.02 tcpserver 0 pop3 /var/qmail/bin/qmail-popup foo.example.net
/usr/local/vpopmail/bin/vchkpw /var/qmail/bin/qmail-pop3d Maildir
```

```
mahe# truss -p 32797
(null)() = 0 (0x0)
sigprocmask(0x1,0xbfbffcc8,0x0) = 0 (0x0)
fork() = 33316 (0x8224)
close(0) = 0 (0x0)
sigprocmask(0x2,0xbfbffcc8,0x0) = 0 (0x0)
```

```
mahe# truss -p 33316
(null)() = 1 (0x1)
read(0x0,0x804bfe0,0x80) = 14 (0xe)
fcntl(0x1,0x3,0x0) = 2 (0x2)
close(2) = 0 (0x0)
fcntl(0x1,0x0,0x2) = 2 (0x2)
close(3) ERR#9 'Bad file descriptor'
pipe() = 3 (0x3)
fork() = 33323 (0x822b)
close(3) = 0 (0x0)
write(4,0x804c100,62) = 62 (0x3e)
close(4) = 0 (0x0)
SIGNAL 20
```

freebsd-isp: Re: vpopmail POP: "ERR aac, chiled crashed" after reboot, core dumped

```
wait4(0x822b,0xbfbffbcc,0x0,0x0) = 33323 (0x822b)
select(0x2,0x0,0xbfbffa38,0x0,0xbfbffa30) = 1 (0x1)
write(1,0x804c080,26) = 26 (0x1a)
exit(0x1) process exit, rval = 256
```

freebsd-isp@freebsd.org mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-isp>

To unsubscribe, send any mail to "freebsd-isp-unsubscribe@freebsd.org"