

Re: Cascading qmail servers

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/net/2003-05/0085.html>

From: Barney Wolff (barney_at_databus.com)

Date: 05/28/03

Date: Wed, 28 May 2003 08:57:55 -0400

To: Ivailo Tanusheff <i.tanusheff@procreditbank.com>

On Wed, May 28, 2003 at 11:29:50AM +0300, Ivailo Tanusheff wrote:

- > *Because of the bandwidth of the mail traffic I'll need to install some*
- > *local mail servers in each office. My question is: how to configure the*
- > *main server and local servers in offices, so each mail send to*
- > *xxx.whatever.com, after receiving by mail.whatever.com to be forwarded*
- > *to the proper mail server. Keep in mind, that there are too many*
- > *accounts to make aliases for each. Also I'll need my users to send*
- > *e-mails trough their local mail servers in the organization and to*
- > *internet. And also I want to keep part of the e-mail accounts on the*
- > *main server for the whatever.com domain itself.*

Don't assume that you can't create an alias for each user. When I worked at a very large NY bank, with well over 100,000 employees, /etc/mail/aliases was that big, and sendmail worked just fine.

--

Barney Wolff <http://www.databus.com/bwresume.pdf>

I'm available by contract or FT, in the NYC metro area or via the 'Net.

freebsd-net@freebsd.org mailing list

<http://lists.freebsd.org/mailman/listinfo/freebsd-net>

To unsubscribe, send any mail to "freebsd-net-unsubscribe@freebsd.org"