

Re: connect() returns EADDRINUSE during massive host->host conn rate

Re: connect() returns EADDRINUSE during massive host->host conn rate

Source: <http://unix.derkeiler.com/Mailing-Lists/FreeBSD/net/2007-11/msg00225.html>

- *From:* Jan Srzednicki <w@xxxxxxxxxx>
 - *Date:* Wed, 28 Nov 2007 19:17:25 +0100
-

On Tue, Nov 27, 2007 at 02:53:20PM +0100, Jan Srzednicki wrote:

Hello,

setting up the relevant fields, setting SO_REUSEADDR and SO_KEEPALIVE, setting O_NONBLOCK on the descriptor. No bind(2) is performed. The connection is initiated from inside a jail (not sure if that implies a internal bind(2) to the jail's address). There are no connections from the other host to the first one.

And some additional info: subsequent connect(s) on the same keep returning EADDRINUSE as well. In order to establish a connection, the application must create a brand new socket and then retry connect().

--

Jan Srzednicki :: <http://wrzask.pl/>
"Remember, remember, the fifth of November"
-- V for Vendetta

freebsd-net@xxxxxxxxxxxxx mailing list
<http://lists.freebsd.org/mailman/listinfo/freebsd-net>
To unsubscribe, send any mail to "freebsd-net-unsubscribe@xxxxxxxxxxxxx"