

[HPADM] Help Me with VA7400 performance.

Source: <http://unix.derkeiler.com/Mailing-Lists/HP-UX-Admin/2003-05/0068.html>

From: Anil Rajapure (anil_unix1975_at_yahoo.com)

Date: 05/19/03

Date: Sun, 18 May 2003 19:40:29 -0700 (PDT)
To: "'hpux admin'" <hpux-admin@dutchworks.nl>

Setup –

VA7400 connected to 4 nodes through fiber hub.

Array configured in 0+1 raid level. Latest firmware updated(HP18) on array. SDM A.1.06.00.

I am trying to improve it's performance by setting LUN accesss depending upon primary controller.

It should be such that the LUN from redudant group-1 will be accessed through it's primary controller.

Used armtopology command on the server where SDM is installed, but how do figure out the primary controller when LUN is allocated to other server.

As said earlier total four nodes access array through two controllers. – for redudancy. I am having difficulty deciding which is the primary controller for each LUN.

Thanks in Advance.

Do you Yahoo!?

The New Yahoo! Search – Faster. Easier. Bingo.

<http://search.yahoo.com>

--

---> Please post QUESTIONS and SUMMARIES only!! <---

To subscribe/unsubscribe to this list, contact majordomo@dutchworks.nl
Name: hpux-admin@dutchworks.nl Owner: owner-hpux-admin@dutchworks.nl

Archives: [ftp.dutchworks.nl:/pub/digests/hpux-admin](ftp://dutchworks.nl/pub/digests/hpux-admin) (FTP, browse only)
<http://www.dutchworks.nl/htbin/hpsysadmin> (Web, browse & search)