

HP-UX-Admin: [HPADM] connect a "ELSA MicroLink 56k" as a support modem

[HPADM] connect a "ELSA MicroLink 56k" as a support modem

Source: <http://unix.derkeiler.com/Mailing-Lists/HP-UX-Admin/2004-01/0041.html>

Paul.Soltermann_at_vonroll-isola.com

Date: 01/23/04

To: hpux-admin@dutchworks.nl
Date: Fri, 23 Jan 2004 12:48:30 +0100

Hallo admins,

I try to connect a "ELSA MicroLink 56k" as a support modem on the "remote" line of the serial port.
Server type 9000/800/L3000-RP5470, HP-UX 11.0.

I read the SUMMARY: How do you connect a modem to an L-class ? I followed the step-by-step description, the problem appeared when I tried to reset the modem.

```
GSP> mr
--> Modem reset filed
```

(Config Settings)

```
Local Console Serial Port bit rate: 9600 bits/s
Local Console Serial Port Flow Control: Software
Local Console Serial Port Terminal Type: hpterm
Remote Console Serial Port Modem Protocol: CCITT
Remote Console Serial Port Modem bit rate: 19200 bits/s
Remote Console Serial Port Modem Flow Control: Software
Remote Console Serial Port Modem Transmit Configuration Strings: Enabled
Remote Console Serial Port Modem Presence: always connected
```

Any idea ?

Paul Soltermann, Isola Werke AG, CH-4226 Breitenbach

--

```
---> Please post QUESTIONS and SUMMARIES only!! <---
To subscribe/unsubscribe to this list, contact majordomo@dutchworks.nl
Name: hpux-admin@dutchworks.nl      Owner: owner-hpux-admin@dutchworks.nl
```

```
Archives:  ftp.dutchworks.nl:/pub/digests/hpux-admin      (FTP, browse only)
            http://www.dutchworks.nl/htbin/hpsysadmin      (Web, browse & search)
```