

[HPADM] mirror root disk/swap

Source: <http://unix.derkeiler.com/Mailing-Lists/HP-UX-Admin/2004-03/0087.html>

From: Hutchins, Greg (ghutchins2_at_selfregional.org)

Date: 03/30/04

Date: Tue, 30 Mar 2004 10:23:12 -0500

To: <hpux-admin@dutchworks.nl>

Hi all,

Getting ready to mirror the root disk and these are the steps that I have gathered to be able to boot off of both disks afterwards. Any input on this process, as it looks fairly straightforward to me. TIA

```
# strings /etc/lvmtab
/dev/vg00
/dev/dsk/c0t6d0
```

```
# ioscan -funC disk
/dev/dsk/c3t6d0
```

```
pvcreate -B /dev/rdisk/c3t6d0
vgextend /dev/vg00 /dev/dsk/c3t6d0
mkboot /dev/rdisk/c3t6d0
mkboot -a "hpux -lq" /dev/rdisk/c3t6d0
mkboot -a "hpux -lq" /dev/rdisk/c0t6d0
lvextend -m 1 /dev/vg00/lvol1 /dev/dsk/c3t6d0
... extend all
setboot -a h/w path
```

Greg Hutchins
Information Technology

--

```
---> Please post QUESTIONS and SUMMARIES only!! <---
To subscribe/unsubscribe to this list, contact majordomo@dutchworks.nl
Name: hpux-admin@dutchworks.nl      Owner: owner-hpux-admin@dutchworks.nl
```

```
Archives:  ftp.dutchworks.nl:/pub/digests/hpux-admin      (FTP, browse only)
           http://www.dutchworks.nl/htbin/hpsysadmin    (Web, browse & search)
```